


Standard scope of delivery Gearbox lubricated for duration of service life, dust-proof package, motor pinion, mounting screws, paper gasket and assembly instructions (adapter plate optional).

Customized versions also available for small quantities.

PLANETARY GEARBOX GPL032P



		2-STAGE	3-STAGE	4-STAGE		
Ratio i:1	Max. motor shaft-ØD	Ratio i:1	Max. motor shaft-ØD	Ratio i:1		Max. motor shaft-ØD
				256	6	
				288	6	
				332.8	6	
		64	6	324	6	
		72	6	400	6	
16	6	81	5	512	6	
18	5	100	6	625	6	
20.8	4	144	5	800	6	
25	3	200	3	1024	6	
32	2	256	2	1600	3	
Rated torque continuous	Type Standard	Nm	4	12	12	
Rated torque intermittent	Type Standard	Nm	6	16	16	
Rated torque continuous	Type V	Nm	6	12	12	
Rated torque intermittent	Type V	Nm	8	16	16	
Max. efficiency at rated torque		%	85	80	75	
Average backlash at no load	Type Standard Type V	arcmin ≤	35	50	60	
Weight without adapter plate		g	180	225	270	
Dimension L		mm	38	47	56	
Dimension A		mm	5.25			
Dimension B		mm	16.25			
Max. radial load	FR 8 mm from shaft end	N	80			
Max. axial load	FA	N	65			
Max. continuous rated speed at drive		min ⁻¹	5000			
Max. intermittent rated speed at drive		min ⁻¹	8000			
Temperature range	Type Standard	°C	-30 / +90			
Temperature range	Type V	°C	-40 / +90			

Type V = heavy duty version

Changes reserved © GYSIN AG | 05/2015